

Nextcloud

docker-compose.yml

```
services:
  mariadb:
    image: mariadb:lts-ubi9
    user: "${APPUSER_PUID}:${APPUSER_PGID}"
    #ports:
    # - 3306:3306
    networks:
      - sky_net
    command: --transaction-isolation=READ-COMMITTED --log-bin=binlog --binlog-format=ROW
    volumes:
      - ${PATH_TO_APPDATA}/nextcloud/db:/var/lib/mysql
    environment:
      - MYSQL_ROOT_PASSWORD=nextcloud
      - MYSQL_PASSWORD=nextcloud
      - MYSQL_DATABASE=nextcloud
      - MYSQL_USER=nextcloud
    restart: always

  nextcloud:
    image: lscr.io/linuxserver/nextcloud:latest
    container_name: nextcloud
    #ports:
    # - 8083:443
    networks:
      - sky_net
    depends_on:
      - mariadb
    environment:
      - PUID=${APPUSER_PUID}
      - PGID=${APPUSER_PGID}
      - TZ=America/Mexico_City
    volumes:
      - ${PATH_TO_APPDATA}/nextcloud/config:/config
```

```
- ${PATH_TO_DATA}/nextcloud/data:/data
- ${PATH_TO_NAS}:/mnt/storage
restart: unless-stopped
```

```
networks:
```

```
  sky_net:
```

```
    driver: bridge
```

```
    external: true
```

```
    name: sky_net
```

.env

```
PATH_TO_APPDATA=
```

```
PATH_TO_DATA=
```

```
PATH_TO_NAS=
```

```
APPUSER_PUID=
```

```
APPUSER_PGID=
```

Revisión #2

Creado 2025-11-27 22:44:18 UTC por Bruno

Actualizado 2025-11-27 22:52:13 UTC por Bruno